

AI Dynamic Face Recognition Attendance & Access Control






-  ✓ Dynamic face recognition
-  ✓ Password
-  ✓ ID/IC card optional

Infrared Live Body Detection

Fast identify forehead, nose, chin, mouth, etc.



- 5000**
ID/IC Card Optional
- 0.5~2.5 meters**
Recognition Distance
- 5000**
Face Capacity
- ≤.02s**
Recognition Speed
- WDR**
2MP Colorful WDR
- 4.3 inch**
Screen Display
- 
Touch Screen
- 
Multi Language
- 
Access Control
- 2MP**
Infrared live camera
- 272*480**
HD Screen
- 99.70%**
Face Recognition Accuracy

Time Attendance Access Control Terminal



Specifications

Screen	4.3 Inch Touch Screen
Keypad	Touch keypad
Operation system	LINUX 4.19
CPU	800M single-core ARM Cortex-A7
NPU	800G (0.8T) Hashrate
RAM, ROM	256M DDR3L, 4G EMMC
Camera	2MP color camera + 2MP infrared camera
Live detection	Dynamic dual-camera anti-counterfeiting, to prevent all kinds of black-and-white, color photos and videos from deception
Logs capacity	500000
Verification	Face recognition, password, ID Card(IC card optional)
Face capacity	5000
Card Capacity	5000
Password Capacity	5000
Face Recognition Accuracy	99.70%
Recognition Speed	≤0.2s
Recognition Distance	0.5~2.5 meters (0.5~1.5 meters with live face recognition on)
Principle of Identification	Face algorithm technology of multi-task cascaded convolutional neural network based on video stream for dynamic face detection, tracking and recognition
WDR	Wide dynamic range, support accurate face recognition under Strong light, dark light and backlight
USB	USB2.0x1, Support U disk import/export data
Power supply	DC12V 1A
Built-in Battery (optional)	7.4V, 2000mA
Network Communication	TCP/IP, USB, Wifi
Free Attendance software	Local software and web based cloud software
Mask Detection	Support mask detection and face recognition with mask on
Access Control Interface	Lock output Doorbell output/external ring Weigand input/output
Environmental adaptability	Working temperature: 0~45°C Working humidity: 20% ~90% Dark enviroment: LEDSoft light automatic fill light (Automatic control according to ambient light)
Muti language	Support 20 national languages and voices including English, Spanish, Arabic, Thai, Farsi, Portuguese, French, Italian, Japanese, Korean, etc