

AI Dynamic Face Recognition Access Control

- ✓ Dynamic face recognition
- ✓ Password
- ✓ ID/IC card optional



5000
Card



Recognition
Distance



5000
Face



Recognition
Speed



2MP Colorful
WDR



Screen
Display



Touch
Screen



Multi
Language



Access
Control



Infrared live
camera




Web Based
Cloud Software



Face Recognition
Accuracy

Support mask detection



LED support LED and infrared light compensation at night

HD Infrared Camera infrared detection camera, make picture automatic exposure and extend identification range

LCD display 4.3 inch touchable LCD display

Card reader

TCP/IP

VCC
GND
EXIT
NO
NC
WG_D0
WG_D1
BEL-
BEL+

26mm 87.5mm

187.5mm

Specifications

Screen	4.3 Inch Touch Screen
Keypad	Touch keypad
Operation system	LINUX 3.10
CPU	800M single-core ARM Cortex-A7
NPU	800G (0.8T) computing power
RAM, ROM	256M DDR3L, 4G EMMC
Camera	2MP color camera + 2MP infrared camera
Live detection	Dynamic dual-camera anti-counterfeiting, to prevent all kinds of black-and-white, color photos and videos from deception
Logs capacity	500000
Verification	Face recognition, password, ID Card(IC card optional)
Face capacity	5000
Card Capacity	5000
Password Capacity	5000
Face Recognition Accuracy	99.70%
Recognition Speed	≤0.2s
Recognition Distance	0.5~2.5 meters (0.5~1.5 meters with live face recognition on)
Principle of Identification	Face algorithm technology of multi-task cascaded convolutional neural network based on video stream for dynamic face detection, tracking and recognition
WDR	Wide dynamic range, support accurate face recognition under Strong light, dark light and backlight
USB	USB2.0x1, Support U disk import/export data
Power supply	DC12V 1A
Network Communication	TCP/IP, USB, WiFi
Free Attendance software	Local software and web based cloud software
Mask Detection	Support mask detection and face recognition with mask on
Access Control Interface	Lock output Doorbell output/external ring/alarm (1 of 3) Weigand input/output
Environmental adaptability	Working temperature: 0~45°C Working humidity: 20% ~90% Dark enviroment: LEDSoft light automatic fill light (Automatic control according to ambient light)
Multi language	Support 20 national languages and voices including English, Spanish, Arabic, Thai, Farsi, Portuguese, French, Italian, Japanese, Korean, etc

